

Pressure loss in INSTAFLEX Klemm-System components (Water 10°C / 2 m/s flow velocity in the outlet cross-section)

Pressure loss in INSTAFLEX Klemm-System components (Water 10°C / 2 m/s flow velocity in the outlet cross-section)

| Art. No. | Catalogue No. | Terms | Symbol | DN/d | ζ -Value | Equivalent pipe length in metres | | | | | | Volume flow accord. W3 Diagr. 1 / gr. LU = 4 1.0 l/s 1.5 l/s 2.0 l/s 2.5 l/s 3.0 l/s 3.5 l/s 4.0 l/s | |
|----------------|---------------|------------------|--------|-------------|----------------|----------------------------------|-----------------|-----------------|-----------------|-----------------|------------------|---|----|
| | | | | | | 1 LU 0.1 l/s | 2 LU 0.2 l/s | 3 LU 0.3 l/s | 4 LU 0.4 l/s | 8 LU 0.5 l/s | 30 LU 0.8 l/s | 60 LU 1.0 l/s | |
| 760.853.140 | | Flow rate | | d16-d20-d16 | 1.5 | 0.53 | 0.63 | 0.69 | 0.74 | 0.79 | -- | -- | -- |
| 760.853.136 | | T-Pieces reducer | | d20-d20-d16 | 1.1 | 0.45 | 0.54 | 0.60 | 0.64 | 0.68 | -- | -- | -- |
| 3355 | | Branch | | d20-d16-d16 | 3.9 | 1.37 | 1.63 | 1.80 | 1.93 | 2.05 | -- | -- | -- |
| 760.853.140 | | | | d20-d20-d16 | 3.5 | 1.23 | 1.46 | 1.62 | 1.74 | 1.84 | -- | -- | -- |
| 760.853.136 | | | | d16 | 1.5 | 0.53 | 0.63 | 0.69 | 0.74 | -- | -- | -- | -- |
| 760.853.124 | 3330 | Coupling | | d20 | 1.2 | 0.49 | 0.59 | 0.65 | 0.70 | 0.74 | -- | -- | -- |
| 760.853.151 | | | | 16 x 2.2 | | 12.80 | 43.50 | 89.90 | 151.30 | -- | -- | -- | -- |
| 3700-3710-3714 | | PB pipe | | 20 x 2.8 | | 4.60 | 15.40 | 31.60 | 52.90 | 79.10 | -- | -- | -- |