



MLCP Tools

Uponor Cutting & Preperation

Uponor Multi pipe cutting tool

- outside diameters 32-40 mm



Item no.	Dimension	Qty 2	Qty 1	UOM
35001089677	32-40	12	1	pce
35001089779	32-40 blade	50	1	pce

Uponor Multi pipe cutting tool

- outside diameters 25-63 mm



Item no.	Dimension	Qty 2	Qty 1	UOM
35001089675	25-63	12	1	pce
35001089777	25-63 blade (wheel)	50	1	pce

Uponor Multi pipe cutting tool

- outside diameters 50-125 mm



Item no.	Dimension	Qty 2	Qty 1	UOM
35001089676	50-125	8	1	pce
35001089778	50-125 blade (wheel)	50	1	pce

Uponor Cutting & Preperation

Uponor MLC pipe cutting + deburring tool



Item no.	Dimension	Qty 2	Qty 1	UOM
35001014334	63-110	32	1	pce
35001014320	63-110 blade (wheel)	100	1	pce

Uponor MLC bevelling tool

- For bevelling the Uponor Uni Pipe PLUS and MLC pipes.
- Supplied with manual toggle. Without manual toggle to be used as attachment for self-driving screw with tapping screw thread.



Item no.	Dimension	Qty 2	Qty 1	UOM
35001006830	16	50	1	pce
35001015749	20	1200	1	pce
35001015756	25	960	1	pce
35001015762	32	900	1	pce

Uponor MLC bevelling tool



Item no.	Dimension	Qty 2	Qty 1	UOM
35001006638	40	600	1	pce
35001015808	50	600	1	pce
35001014339	63	600	1	pce
35001014344	75	600	1	pce

Uponor MLC bevelling tool

- For bevelling the Uponor Uni Pipe PLUS and MLC pipes.



Item no.	Dimension	Qty 2	Qty 1	UOM
35001015739	16/20/25	60	1	pce

Uponor MLC deburring tool universal



Item no.	Dimension	Qty 2	Qty 1	UOM
35001060167		50	1	pce

Uponor Cutting & Preperation

Uponor MLC bending spring inside

- bending spring for Uponor Uni Pipe PLUS and MLC pipes.



Item no.	Dimension	Qty 2	Qty 1	UOM
35001013729	16	100	1	pce
35001013734	20	75	1	pce
35001013737	25	50	1	pce
35001013739	32	40	1	pce

Uponor MLC bending spring outside

- bending spring for Uponor Uni Pipe PLUS and MLC pipes.



Item no.	Dimension	Qty 2	Qty 1	UOM
35001006639*	14	550	1	pce
35001006640	16	55	1	pce
35001013792	20	45	1	pce
35001013794	25	45	1	pce

Uponor Uni Pipe PLUS bending tool

- producing evenly formed bends in Uponor Uni Pipe PLUS pipes with outer diameters up to 32 mm.
- Delivered complete in tool case with bending segments.



Item no.	Dimension	Qty 2	Qty 1	UOM
35001071925	16-32	100	1	pce

Uponor Pressing

Uponor S-Press manual tool w/o inserts

- in conjunction with exchangeable inserts
- Supplied in case without exchangeable inserts



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
35001015764	16-20	16-20	100	1	pce

Uponor S-Press manual tool insert

- For inserting into the manual pressing tool



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
35001015777	16	16	50	1	pce
35001015780	20	20	50	1	pce

Uponor S-Press tool UP110 without jaws

- supplied in carrying case, complete with battery and charger unit
- without pressing jaws.
- Range of application up to 110 mm.

Technical specifications:

- Quick pressing due to short pressing cycle
- Crimping force: linear thrust of approx. 32 kN
- Battery capacity: High-power Makita 3.0 Ah Li-Ion battery
- Charging time: 22 min
- Weight incl. battery: without jaw 3.5 kg
- Dimensions tool: 366 x 81 x 317 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 2	Qty 1	UOM
35001083612		20	1	set

Uponor S-Press battery UP110

- Akku 18 V / 3,0 Ah, Li-Ion (54 Wh)
- Battery voltage: 18 V
- Battery capacity: 3.0 Ah
- Charging time: With SPI S-PRESS BATTERY CHARGER: 22 min
- Cell technology: Li-Ion
- Weight: 0,6 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
35001083608*		18	10	1	pce

Uponor Pressing

Uponor S-Press battery charger

- Quick-charger for 18V Li-Ion batteries, 230 V
- Charging time: 1.3 Ah 15 min,
3.0 Ah 22 min
- Mains supply: 230 V AC
- Voltage range: 18 V
- Weight: 1,0 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
35001083610*	Mini2, UP110	230	72	1	pce

Uponor S-Press electric tool w/o jaws UP75

Technical specifications:

- Weightl: 3.30 kg
- Nominal voltage: 230 V AC / 50 Hz
- Nominal capacity: 200 Watt
- Press power: ca. 32 kN
- Press duration: ca. 7 sec.



Item no.	Dimension	d mm	OV V	Qty 2	Qty 1	UOM
35001007082	-	110	230	20	1	pce

Uponor S-Press spare battery UP75

- for the battery powered pressing machine UP 75
- Not compatible to the Ni-Cd charger unit.



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
35001006949*		12	12	1	pce

Uponor S-Press spare charger Mini UP75

- or the re-chargable battery of the pressing machine UP 75 and Mini KSP0



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
35001006950		230	10	1	pce

Uponor S-Press jaw UPP1

- pressing jaws for Uponor MLC press fittings



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
35001007084	16	16	216	1	pce
35001007086	20	20		1	pce
35001007087	25	25		1	pce
35001007088	32	32		1	pce

Uponor Pressing

Uponor S-Press jaw UPP1

- pressing jaws for Uponor MLC press fittings



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
35001015768	40	40	108	1	pce
35001015792	50	50	108	1	pce

Uponor S-Press base unit for chain

- Base unit for the pressing chain to press Uponor MLC press fittings 63 - 110 in conjunction with the pressing tool UP 110, UP 75 and UP 75 EL



Item no.	Dimension	d mm	Qty 1	UOM
35001046545	63-110	63-110	1	pce

Uponor S-Press chain

- pressing chain to be used together with the Base unit to press Uponor MLC press fittings 63 - 110 in conjunction with the pressing tool UP 110, UP 75 and UP 75 EL



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
35001046541	63	63	72	1	pce
35001046542	75	75	72	1	pce
35001046543*	90	90	72	1	pce
35001046544*	110	110	54	1	pce

Uponor Pressing

Uponor S-Press tool Mini2 with KSP0 jaw

- Uponor S-Press tool Mini² supplied in carrying case, complete with battery and charger unit and pressing jaws.
- Range of application up to 32 mm.

Technical specifications:

- Very quick pressing thanks to short pressing cycle of 3-4 seconds
- Crimping force: linear thrust of approx. 15 kN
- Battery capacity: High-power Makita 1.3 Ah Li-Ion battery (3.0 Ah optional)
- Charging time: 1.5 Ah 15 min. 3.0 Ah 22 min
- Weight incl. battery: without jaws 1.7 kg
- Dimensions tool: 377 x 75 x 116 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 2	Qty 1	UOM
35001083586	16/20/25/32	30	1	set

Uponor S-Press tool Mini2 with KSP0 jaw

- Uponor S-Press tool Mini² supplied in carrying case, complete with battery and charger unit and pressing jaws.
- Range of application up to 25 mm.

Technical specifications:

- Very quick pressing thanks to short pressing cycle of 3-4 seconds
- Crimping force: linear thrust of approx. 15 kN
- Battery capacity: High-power Makita 1.3 Ah Li-Ion battery (3.0 Ah optional)
- Charging time: 1.5 Ah 15 min. 3.0 Ah 22 min
- Weight incl. battery: without jaws 1.7 kg
- Dimensions tool: 377 x 75 x 116 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 2	Qty 1	UOM
35001083594	16/20/25	25	1	set

Uponor Pressing

Uponor S-Press tool Mini2 without jaws

- Uponor S-Press tool Mini² supplied in carrying case, complete with battery and charger unit.
- Range of application up to 32 mm.

Technical specifications:

- Very quick pressing thanks to short pressing cycle of 3-4 seconds
- Crimping force: linear thrust of approx. 15 kN
- Battery capacity: High-power Makita 1.5 Ah Li-Ion battery (3.0 Ah optional)
- Charging time: 1.5 Ah 15 min. 3.0 Ah 22 min
- Weight incl. battery: without jaws 1.7 kg
- Dimensions tool: 377 x 75 x 116 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder



Item no.	Dimension	Qty 1	UOM
35001085388		1	pce

Uponor S-Press tool Mini2

- Uponor SPI S-Press tool Mini² without carrying case, without battery and charger unit and without pressing jaws.



Item no.	Dimension	Qty 1	UOM
13500087260		1	pce

Uponor S-Press battery Mini2

- Battery 18 V / 1.5 Ah, Li-Ion (27 Wh)
- Battery voltage: 18 V
- Battery capacity: 1.5 Ah
- Charging time: With SPI S-Press Battery Charger: 15 min
- Cell technology: Li-Ion
- Weight: 0,4 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
35001083605		18	48	1	pce

Uponor S-Press battery charger

- Quick-charger for 18V Li-Ion batteries, 230 V
- Charging time: 1.3 Ah 15 min,
3.0 Ah 22 min
- Mains supply: 230 V AC
- Voltage range: 18 V
- Weight: 1,0 kg



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
35001083610*	Mini2, UP110	230	72	1	pce

Uponor Pressing

Uponor S-Press battery Mini

- Battery: 9.6V for Uponor battery pressing tool Mini KSP0.



Item no.	Dimension	OV V	Qty 2	Qty 1	UOM
35001015703		9,6	120	1	pce

Uponor S-Press jaw Mini KSP0

- Uponor pressing jaws MLC Mini KSP0



Item no.	Dimension	d mm	Qty 2	Qty 1	UOM
35001007091*	16	16	5	1	pce
35001007093*	20	20	5	1	pce
35001007094*	25	25	5	1	pce
35001007095*	32	32	5	1	pce

Uponor Accessories

Uponor Smart Aqua mounting rack bending tool

- For bending the 2 meter long mounting track.



Item no.	Dimension	Qty 2	Qty 1	UOM
35001015424	2m	100	1	pce

Uponor plastic pipe bend support

Made of impact resistant plastic as bend support 90° bends.



Item no.	Dimension	d mm	r mm	Qty 2	Qty 1	UOM
35001009004	16	16	90	2340	10	pce
35001009233	20	20	100	2340	10	pce

Uponor Galvanised Steel pipe bend support

Made of galvanised steel as bend support 90° bends.



Item no.	Dimension	d mm	r mm	Qty 2	Qty 1	UOM
35001009006	25 Galv. Steel	20	90	5000	20	pce



Uponor GmbH

P.O. Box 1641
97433 Hassfurt
Germany

Australia

T +49-(0)9521 690 0
F +49-(0)9521 690 750
E international@uponor.com

T +61 (0)7 3202 6831
M +61 (0)477 136 977
E international@uponor.com

