



Multilayer Pipe Systems

Uponor Uni Pipe PLUS



The Uni Pipe PLUS is Uponor's unique multilayer composite pipe for tap water and heating/cooling application. Its bend radius is up to 40 per cent smaller than current multilayer composite pipes: changes of

direction when installing can be achieved by bending the pipe, reducing fitting requirements and installation time.

Your benefits

- Seamless or OWC-technology for highest level of safety
- High dimensional stability, low expansion rates
- Increased flexibility
- 100% oxygen barrier
- Lightweight



Specification

- Oxygen diffusion resistant multi-layer composite pipe (PE-RT - adhesive – seamless aluminium/longitudinally welded aluminium - adhesive - PE-RT) produced using SACP and OWC-technology.
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according to EN 806.

Application


- Tested/Approved according to EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar
- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

- WaterMark Certified to AS 4176.2:2010 Multilayer pipes for pressure application Part 2: Multilayer piping Systems for hot and cold water plumbing applications- Pipes (ISO 21003-2:2008, MOD)
- AS 4176.3:2010 Multilayer pipes for pressure applications Part 3: Multilayer piping systems for hot and cold water plumbing applications—Fittings (ISO 21003-3:2008, MOD)




Uponor Uni Pipe PLUS white S



Item no.	Dimension	L do s m mm mm	Qty 2	Qty 1	UOM
35001059572	16x2,0 5m	5 16 2,0	125	5	m
35001059573	20x2,25 5m	5 20 2,25	85	5	m
35001059574	25x2,5 5m	5 25 2,5	50	5	m
35001059575	32x3,0 5m	5 32 3	35	5	m

Uponor MLC pipe white S

- bar




Item no.	Dimension	L do s m mm mm	Qty 2	Qty 1	UOM
35001013446	40x4,0 5m	5 40 4	20	5	m
35001013449	50x4,5 5m	5 50 4,5	20	5	m
35001013451	63x6,0 5m	5 63 6	15	5	m
35001013453	75x7,5 5m	5 75 7,5	255	5	m
35001013455	90x8,5 5m	5 90 8,5	255	5	m
35001013457	110x10,0 5m	5 110 10	165	5	m

Uponor Uni Pipe PLUS

Uponor Uni Pipe PLUS white

- coil



Item no.	Dimension	L m	do mm	s mm	Qty 2	Qty 1	UOM
35001059576	16x2,0 100m	100	16	2,0	2000	100	m
35001059578	16x2,0 500m	500	16	2,0	3500	500	m
35001059577	16x2,0 200m	200	16	2	2600	200	m
35001059579	20x2,25 100m	100	20	2,25	1300	100	m
35001059581	25x2,5 50m	50	25	2,5	700	50	m
35001059583	32x3,0 50m	50	32	3	400	50	m

Uponor Uni Pipe PLUS


Uponor Uni Pipe PLUS insulated

Specification

- Consists of pipe and insulating layer.
- Supplied in coils.
- pipe insulation made of polyethylene foam with closed-cell material structure.
- With sturdy, seamless foil coating

Uponor Uni Pipe PLUS white insulated S10 WLS 035


- coil
- Insulation thickness 10 mm
- thermal conductivity $\lambda=0,035 \text{ W/m}^{\circ}\text{K}$
- round extruded



Item no.	Dimension	L m	do mm	do1 mm	s mm	s1 mm	colour	Qty 2	Qty 1	UOM
35001062181	16x2,0 blue 75m	75	16	36	2	10	blue	450	75	m
35001062182	20x2,25 blue 75m	75	20	40	2,25	10	blue	525	75	m
35001062183	25x2,5 blue 50m	50	25	45	2,5	10	blue	350	50	m

Uponor Uni Pipe PLUS white insulated S13 BL-S2-D0


- coil
- Insulation thickness 13 mm
- thermal conductivity $\lambda=0,04 \text{ W/m}^{\circ}\text{K}$
- round extruded



Item no.	Dimension	L m	do mm	do1 mm	s mm	s1 mm	colour	Qty 2	Qty 1	UOM
35001093952	16x2,0 blue 75m	75	16	42	2	13	blue	450	75	m
35001093953	16x2,0 red 75m	75	16	42	2	13	red	450	75	m
35001093954	20x2,25 blue 75m	75	20	46	2,25	10	blue	450	75	m
35001093955	20x2,25 red 75m	75	20	46	2,25	10	red	450	75	m
35001094883	25x2,5 blue 50m	50	25	51	2,5	10	blue	200	50	m

Uponor Uni Pipe PLUS white insulated S15 Clima


- coil
- Insulation thickness 15 mm
- thermal conductivity $\lambda=0,040 \text{ W/m}^{\circ}\text{K}$
- round extruded



Item no.	Dimension	L m	do mm	do1 mm	s mm	s1 mm	colour	Qty 2	Qty 1	UOM
35001088239	32x3,0 blue 25m	23	32	62	3	15	blue	225	25	m


Uponor Uni Pipe PLUS white in conduit

- pipe in conduit



Item no.	Dimension	L m	di1 mm	do mm	do1 mm	s mm	colour	Qty 2	Qty 1	UOM
35001063059	16x2,0 - 25/20 blue 75m	75	20	16	25	2,0	blue	1125	75	m
35001063060	20x2,25 - 28/23 blue 75m	75	23	20	28	2,25	blue	900	75	m
35001063061	16x2,0 - 25/20 red 75m	75	20	16	25	2,0	red	1125	75	m
35001063062	20x2,25 - 28/23 red 75m	75	23	20	28	2,25	red	900	75	m

Uponor S-Press PLUS



S-Press PLUS/ S-Press, our new generation of press fittings, is the perfect solution for ensuring permanently tight pipe connections. It's 100% backward compatible with current Uponor composite pipes and tools.

Available in dimensions from 16 to 75 mm in both metal and plastic, S-Press PLUS/ S-Press are the fittings that knows no compromise.

Your benefits

- **TOUGH:** Withstand harshest conditions
- **SAFE:** Ensuring your perfect pressing result
- **EASY:** Simplifying planning and installation
- **SMART:** Answering all your questions on site



Specification

- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification

- WaterMark Certified to AS 4176.2:2010 Multilayer pipes for pressure application Part 2: Multilayer piping Systems for hot and cold water plumbing applications- Pipes (ISO 21003-2:2008, MOD)
- AS 4176.3:2010 Multilayer pipes for pressure applications Part 3: Multilayer piping systems for hot and cold water plumbing applications—Fittings (ISO 21003-3:2008, MOD)



Uponor S-Press PLUS/ S-Press made of PPSU


Specification

- made of PPSU

Uponor S-Press PLUS

Uponor S-Press PLUS elbow PPSU


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code



Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001039929	16-16	33	33	13	13	80	20	pce
35001039930	20-20	37	37	16	16	80	10	pce
35001039931	25-25	48	48	19	19	80	10	pce
35001039932	32-32	51	51	23	23	20	5	pce

Uponor S-Press composite elbow PPSU


- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001046386	40-40	68	68	29	29	960	5	pce
35001046387	50-50	73	73	34	34	576	3	pce
35001032877	63-63	101	101	40	40	210	1	pce
35001032878	75-75	108	108	47	47	210	1	pce

Uponor S-Press composite elbow 45° PPSU

- Fast installation with easy bevel and without calibration
- Colour code




Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001046388	40-40	56	56	17	17	960	5	pce
35001046389	50-50	59	59	20	20	576	3	pce
35001032879	63-63	83	83	23	23	192	1	pce
35001032880	75-75	86	86	25	25	192	1	pce

Uponor S-Press PLUS

Uponor S-Press PLUS coupling PPSU


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code



Item no.	Dimension	L mm	L1 mm	L2 mm	z1 mm	Qty 2	Qty 1	UOM
35001039933	16-16	51	20	20	11	80	20	pce
35001039934	20-20	54	21	21	11	80	10	pce
35001039935	25-25	68	28	28	11	80	10	pce
35001039936	32-32	69	28	28	13	80	10	pce

Uponor S-Press composite coupling PPSU


- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	L mm	L1 mm	L2 mm	z1 mm	Qty 2	Qty 1	UOM
35001046401	40-40	91	39	39	13	960	5	pce
35001046402	50-50	91	39	39	13	576	3	pce
35001032881	63-63	137	61	61	15	384	1	pce
35001032882	75-75	137	61	61	15	384	1	pce

Uponor S-Press PLUS reducer PPSU

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code




Item no.	Dimension	L mm	L1 mm	L2 mm	z1 mm	Qty 2	Qty 1	UOM
35001039937	20-16	53	21	20	11	80	20	pce
35001039938	25-16	60	28	20	11	80	10	pce
35001039939	25-20	61	28	21	11	80	10	pce
35001039940	32-25	69	28	28	13	80	10	pce

Uponor S-Press PLUS

Uponor S-Press reducer PPSU


- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l mm	l1 mm	l2 mm	z1 mm	Qty 2	Qty 1	UOM
35001039941	40-25	80	39	28	12	960	5	pce
35001039942	40-32	80	39	28	13	960	5	pce
35001039943	50-32	80	39	28	13	1152	3	pce
35001046406	50-40	91	39	39	13	576	3	pce
35001032883	63-40	115	61	37	17	384	1	pce
35001032884	63-50	115	61	37	17	384	1	pce
35001032885	75-50	115	61	37	17	384	1	pce
35001032886	75-63	137	61	59	17	384	1	pce

Uponor S-Press PLUS tee PPSU


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code



Item no.	Dimension	l1 mm	l2 mm	l3 mm	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001039944	16-16-16	33	33	33	13	13	13	80	10	pce
35001039945	20-20-20	37	37	37	16	16	16	80	10	pce
35001039946	25-25-25	48	48	48	19	19	19	20	5	pce
35001039947	32-32-32	51	51	51	23	23	23	20	5	pce

Uponor S-Press composite tee PPSU

- Fast installation with easy bevel and without calibration
- Colour code




Item no.	Dimension	l1 mm	l2 mm	l3 mm	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001046390	40-40-40	68	68	68	29	29	29	720	5	pce
35001046391	50-50-50	73	73	73	33	33	33	288	3	pce
35001032887	63-63-63	101	101	101	42	40	42	150	1	pce
35001032888	75-75-75	108	107	108	47	47	47	150	1	pce

Uponor S-Press PLUS

Uponor S-Press PLUS tee red. PPSU


- Fixed stainless steel sleeve
- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code



Item no.	Dimension	l1 mm	l2 mm	l3 mm	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001039948	16-20-16	35	35	35	15	13	15	80	10	pce
35001039949	20-16-16	37	36	36	16	16	16	80	10	pce
35001039950	20-16-20	37	36	37	16	16	16	80	10	pce
35001039951	20-20-16	37	37	36	16	16	16	80	10	pce
35001039952	20-25-20	41	48	41	19	19	19	80	10	pce
35001039953	25-16-16	48	39	39	19	19	19	80	10	pce
35001039954	25-16-20	48	39	41	19	19	19	80	10	pce
35001039955	25-16-25	48	39	48	19	19	19	80	10	pce
35001039956	25-20-20	48	41	41	19	19	19	80	10	pce
35001039957	25-20-25	48	41	48	19	19	19	80	10	pce
35001039958	32-16-32	51	43	51	23	23	23	20	5	pce
35001039959	32-20-32	51	44	51	23	23	23	20	5	pce
35001039960	32-25-25	51	51	51	23	23	23	20	5	pce
35001039961	32-25-32	51	51	51	23	23	23	20	5	pce

Uponor S-Press tee red. PPSU


- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l1 mm	l2 mm	l3 mm	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001039962	40-20-40	68	49	68	29	28	29	960	5	pce
35001039963	40-25-32	68	56	56	29	28	28	960	5	pce
35001039964	40-25-40	68	56	68	29	28	29	720	5	pce
35001039965	40-32-32	68	56	56	29	28	28	960	5	pce
35001039966	40-32-40	68	56	68	29	28	29	720	5	pce
35001039967	50-25-40	73	61	73	34	33	34	432	3	pce
35001039968	50-25-50	73	61	73	34	33	34	432	3	pce
35001039969	50-32-50	73	61	73	34	33	34	432	3	pce

Uponor S-Press composite tee reducer PPSU

- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l1 mm	l2 mm	l3 mm	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001046400	50-40-50	73	73	73	33	33	33	288	3	pce
35001032889	63-25-63	101	68	101	40	39	40	150	1	pce
35001032890	63-32-63	101	68	101	40	39	40	150	1	pce
35001032891	63-40-63	101	79	101	40	40	40	150	1	pce
35001032892	75-32-75	108	74	108	47	45	47	150	1	pce
35001032893	75-40-75	108	86	108	47	44	47	150	1	pce
35001032894	75-50-75	108	86	108	47	49	47	150	1	pce

Uponor S-Press PLUS


Uponor S-Press PLUS

Specification

- made of tin-plated DR brass

Uponor S-Press PLUS adapter male thread


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	L mm	L1 mm	L2 mm	R inch	z1 mm	Qty 2	Qty 1	UOM
35001070502	16-R $\frac{1}{2}$ "MT	44	14	20	$\frac{1}{2}$	10	80	20	pce
35001070503	16-R $\frac{3}{4}$ "MT	46	16	20	$\frac{3}{4}$	11	120	15	pce
35001070504	20-R $\frac{1}{2}$ "MT	45	14	21	$\frac{1}{2}$	10	80	20	pce
35001070505	20-R $\frac{3}{4}$ "MT	48	15	21	$\frac{3}{4}$	11	80	10	pce
35001070506	20-R1"MT	54	17	21	1	16	80	10	pce
35001070507	25-R $\frac{3}{4}$ "MT	55	15	28	$\frac{3}{4}$	11	80	10	pce
35001070508	25-R1"MT	62	18	28	1	16	40	5	pce
35001070509	32-R1"MT	62	17	28	1	16	40	5	pce
35001070510	32-R1 $\frac{1}{4}$ "MT	66	19	28	1 $\frac{1}{4}$	19	20	5	pce

Uponor S-Press adapter male thread

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code




Item no.	Dimension	L mm	L1 mm	L2 mm	R inch	z1 mm	d mm	Qty 2	Qty 1	UOM
35001046901	40-R1 $\frac{1}{4}$ "MT	78	20	38	1 $\frac{1}{4}$	20		960	5	pce
35001046902	40-R1 $\frac{1}{2}$ "MT	80	20	38	1 $\frac{1}{2}$	22	40	960	5	pce
35001046905	50-R1 $\frac{1}{2}$ "MT	80	20	38	1 $\frac{1}{2}$	22	50	1152	3	pce
35001046906	50-R2"MT	84	24	38	2	22	50	576	3	pce
35001032895	63-R2"MT	111	28	61	2	22		336	1	pce
35001032896	75-R2 $\frac{1}{2}$ "MT	110	27	61	2 $\frac{1}{2}$	22		336	1	pce

Uponor S-Press PLUS

Uponor S-Press PLUS adapt. female thread


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	l	l1	l2	Rp	z1		Qty 2	Qty 1	UOM
35001070515	16-Rp½"FT	47	15	20	½	12		80	20	pce
35001070516	20-Rp½"FT	47	15	21	½	10		120	15	pce
35001070517	20-Rp¾"FT	51	16	21	¾	14		80	10	pce
35001070518	20-Rp1"FT	52	19	21	1	12		80	20	pce
35001070519	25-Rp¾"FT	56	17	28	¾	11		40	5	pce
35001070520	25-Rp1"FT	59	19	28	1	12		40	5	pce
35001070521	32-Rp1"FT	58	20	28	1	10		40	5	pce
35001070522	32-Rp1 ¼"FT	62	21	28	1 ¼	13		20	5	pce

Uponor S-Press adapter female thread

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code




Item no.	Dimension	l	l1	l2	Rp	z1		Qty 2	Qty 1	UOM
35001046903	40-Rp1 ¼"FT	73	21	38	1 ¼	14		960	5	pce
35001046904	40-Rp1 ½"FT	77	21	38	1 ½	18		960	5	pce
35001046907	50-Rp1 ½"FT	73	21	38	1 ½	14		1152	3	pce

Uponor S-Press PLUS

Uponor S-Press PLUS elbow


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001070523	16-16	34	34	14	14	80	20	pce
35001070524	20-20	37	37	16	16	80	10	pce
35001070525	25-25	47	47	19	19	40	5	pce
35001070526	32-32	51	51	23	23	20	5	pce

Uponor S-Press elbow


- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001046908	40-40	72	72	34	34	600	5	pce
35001046911	50-50	79	79	41	41	240	3	pce

Uponor S-Press PLUS bend

- Made of casted DR brass
- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- extra low pressure loss




Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001070527	16-16	37	37	17	17	80	10	pce
35001070528	20-20	40	40	19	19	80	10	pce
35001070529	25-25	50	50	22	22	40	5	pce
35001070530	32-32	56	56	28	28	20	5	pce

Uponor S-Press PLUS

Uponor S-Press PLUS elbow male thread


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	l1 mm	l2 mm	R inch	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001070532	16-R $\frac{1}{2}$ "MT	30	37	$\frac{1}{2}$	15	17	80	20	pce
35001070533	20-R $\frac{1}{2}$ "MT	32	41	$\frac{1}{2}$	15	19	80	10	pce
35001070534	20-R $\frac{3}{4}$ "MT	34	41	$\frac{3}{4}$	18	19	80	10	pce
35001070535	25-R $\frac{3}{4}$ "MT	36	48	$\frac{3}{4}$	20	19	40	5	pce
35001070536	25-R1"MT	43	51	1	22	23	40	5	pce
35001070537	32-R1"MT	43	51	1	22	23	20	5	pce

Uponor S-Press elbow adapter male thread


- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l1 mm	l2 mm	R inch	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001046909	40-R1 $\frac{1}{4}$ "MT	49	72	1 $\frac{1}{4}$	30	34	500	5	pce

Uponor S-Press PLUS elbow female thread

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access




Item no.	Dimension	l1 mm	l2 mm	Rp inch	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001070539	16-Rp $\frac{1}{2}$ "FT	33	38	$\frac{1}{2}$	18	18	80	10	pce
35001070540	20-Rp $\frac{1}{2}$ "FT	36	41	$\frac{1}{2}$	21	19	80	10	pce
35001070541	20-Rp $\frac{3}{4}$ "FT	36	43	$\frac{3}{4}$	19	22	40	10	pce
35001070542	25-Rp $\frac{3}{4}$ "FT	40	50	$\frac{3}{4}$	23	22	20	5	pce
35001070543	25-Rp1"FT	45	54	1	25	26	20	5	pce
35001070544	32-Rp1"FT	49	54	1	30	26	20	5	pce

Uponor S-Press PLUS

Uponor S-Press elbow adap. female thread


- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l1 mm	l2 mm	Rp inch	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001046910	40-Rp1 ½"FT	59	75	1 ½	38	37	500	5	pce
35001046912	50-Rp1 ½"FT	59	79	1 ½	38	41	300	3	pce

Uponor S-Press PLUS elbow 45


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001070545	25-25	46	46	18	18	20	5	pce
35001070546	32-32	49	49	23	23	20	5	pce

Uponor S-Press elbow 45

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code




Item no.	Dimension	l1 mm	l2 mm	z1 mm	z2 mm	Qty 2	Qty 1	UOM
35001046913	40-40	59	59	21	21	500	5	pce
35001046914	50-50	63	63	25	25	300	3	pce

Uponor S-Press PLUS

Uponor S-Press PLUS coupling


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	l mm	l1 mm	l2 mm	z1 mm	Qty 2	Qty 1	UOM
35001070547	16-16	51	20	20	12	80	20	pce
35001070548	20-20	54	21	21	12	80	10	pce
35001070549	25-25	68	28	28	12	80	10	pce
35001070550	32-32	68	28	28	12	40	5	pce

Uponor S-Press coupling


- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



Item no.	Dimension	l mm	l1 mm	l2 mm	z1 mm	Qty 2	Qty 1	UOM
35001046932	40-40	88	38	38	12	960	5	pce
35001046935	50-50	88	38	38	12	576	3	pce

Uponor S-Press PLUS reducer

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access




Item no.	Dimension	l mm	l1 mm	l2 mm	z1 mm	Qty 2	Qty 1	UOM
35001070552	20-16	53	21	20	12	80	20	pce
35001070553	25-16	60	28	20	12	80	10	pce
35001070554	25-20	61	28	21	12	80	10	pce
35001070555	32-20	61	28	21	12	80	10	pce
35001070556	32-25	68	28	28	12	80	10	pce

Uponor S-Press PLUS

Uponor S-Press reducer


- Made of tin-plated brass



Item no.	Dimension	l	l1	l2	z1		Qty 2	Qty 1	UOM
35001046934	50-40	89	38	38	14		576	3	pce

Uponor S-Press PLUS tee


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	l1	l2	l3	z1	z2	z3		Qty 2	Qty 1	UOM
35001070560	16-16-16	34	34	34	14	14	14		80	10	pce
35001070561	20-20-20	37	37	37	16	16	16		80	10	pce
35001070562	25-25-25	47	47	47	19	19	19		20	5	pce
35001070563	32-32-32	51	51	51	23	23	23		20	5	pce

Uponor S-Press tee

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code




Item no.	Dimension	l1	l2	l3	z1	z2	z3		Qty 2	Qty 1	UOM
35001046921	40-40-40	72	72	72	34	34	34		400	5	pce
35001046928	50-50-50	79	79	79	41	41	41		300	3	pce

Uponor S-Press PLUS

Uponor S-Press PLUS tee reducer

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access




Item no.	Dimension	l1 mm	l2 mm	l3 mm	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001070566	16-20-16	36	37	36	16	16	16	80	10	pce
35001070567	20-16-16	35	36	34	14	16	14	40	10	pce
35001070568	20-16-20	35	36	35	14	16	14	80	20	pce
35001070569	20-20-16	37	37	36	16	16	16	80	20	pce
35001070570	20-25-16	40	47	38	19	19	19	40	10	pce
35001070571	20-25-20	40	47	40	19	19	19	40	10	pce
35001070572	25-16-16	44	38	36	16	19	17	40	5	pce
35001070573	25-16-20	44	38	38	16	19	17	40	5	pce
35001070574	25-16-25	42	38	42	14	19	14	20	5	pce
35001070575	25-20-16	44	40	36	16	19	17	40	5	pce
35001070576	25-20-20	44	40	38	16	19	17	40	5	pce
35001070577	25-20-25	44	40	44	16	19	16	20	5	pce
35001070578	25-25-16	47	47	38	19	19	19	20	5	pce
35001070579	25-32-25	50	48	50	22	20	22	20	5	pce
35001070580	32-16-32	43	42	43	15	22	15	20	5	pce
35001070581	32-20-32	45	43	45	17	22	17	20	5	pce
35001070582	32-25-25	48	50	48	20	22	20	20	5	pce
35001070583	32-25-32	48	50	48	20	22	20	20	5	pce

Uponor S-Press PLUS

Uponor S-Press PLUS tee male thread


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	L1 mm	L2 mm	L3 mm	R inch	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001070592	16-R $\frac{1}{2}$ "MT-16	38	30	38	$\frac{1}{2}$	18	15	18	40	10	pce
35001070593	25-R $\frac{3}{4}$ "MT-25	48	36	48	$\frac{3}{4}$	19	21	19	20	5	pce
35001070594	32-R $\frac{3}{4}$ "MT-32	48	40	48	$\frac{3}{4}$	19	25	19	20	5	pce

Uponor S-Press PLUS tee female thread


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access



Item no.	Dimension	L1 mm	L2 mm	L3 mm	Rp inch	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001070595	16-Rp $\frac{1}{2}$ "FT-16	38	33	38	$\frac{1}{2}$	18	18	18	40	10	pce
35001070596	20-Rp $\frac{1}{2}$ "FT-20	40	35	40	$\frac{1}{2}$	19	20	19	60	15	pce
35001070597	20-Rp $\frac{3}{4}$ "FT-20	43	37	43	$\frac{3}{4}$	22	20	22	40	10	pce
35001070598	25-Rp $\frac{1}{2}$ "FT-25	48	37	48	$\frac{1}{2}$	19	22	19	20	5	pce
35001070599	25-Rp $\frac{3}{4}$ "FT-25	50	40	50	$\frac{3}{4}$	22	23	22	20	5	pce
35001070600	32-Rp $\frac{1}{2}$ "FT-32	47	40	47	$\frac{1}{2}$	18	25	18	20	5	pce
35001070601	32-Rp $\frac{3}{4}$ "FT-32	51	44	51	$\frac{3}{4}$	23	27	23	20	5	pce

Uponor S-Press tee adapter female thread

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code




Item no.	Dimension	L1 mm	L2 mm	L3 mm	Rp inch	z1 mm	z2 mm	z3 mm	Qty 2	Qty 1	UOM
35001046922	40-Rp $\frac{1}{2}$ "FT-40	69	47	69	$\frac{1}{2}$	31	30	31	500	5	pce
35001046923	40-Rp $\frac{3}{4}$ "FT-40	64	47	64	$\frac{3}{4}$	26	31	26	400	5	pce
35001046929	50-Rp1"FT-50	72	56	72	1	34	37	34	240	3	pce

Uponor S-Press PLUS

Uponor S-Press PLUS adapter swivel nut


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Releasable screw connector for connection to on-wall fittings, filters and shut-off valves
- Thread acc. to EN ISO 228-1.



Item no.	Dimension	l mm	l1 mm	l2 mm	G inch	z1 mm	Qty 2	Qty 1	UOM
35001070602	16-G $\frac{1}{2}$ "SN	53	8	20	$\frac{1}{2}$	25	30	1	pce
35001070603	16-G $\frac{3}{4}$ "SN	44	8	20	$\frac{3}{4}$	17	20	1	pce
35001070604	20-G $\frac{1}{2}$ "SN	59	8	21	$\frac{1}{2}$	30	20	1	pce
35001070605	20-G $\frac{3}{4}$ "SN	46	8	21	$\frac{3}{4}$	17	20	1	pce
35001070606	25-G $\frac{3}{4}$ "SN	64	8	28	$\frac{3}{4}$	28	15	1	pce
35001070607	25-G1"SN	57	9	28	1	20	15	1	pce
35001070610	32-G1 $\frac{1}{4}$ "SN	59	9	28	1 $\frac{1}{4}$	22	10	1	pce

Uponor S-Press adapter swivel nut

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code
- Releasable screw connector for connection to on-wall fittings, filters and shut-off valves
- Thread acc. to EN ISO 228-1.




Item no.	Dimension	l mm	l1 mm	l2 mm	G inch	z1 mm	Qty 2	Qty 1	UOM
35001046937	40-G1 $\frac{1}{2}$ "SN	77	10	38	1 $\frac{1}{2}$	30	960	5	pce
35001046939	50-G2"SN	82	12	38	2	32	576	3	pce

Uponor S-Press PLUS

Uponor S-Press PLUS tap elbow M


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- for on wall installation or attachment with rotation protection to the Uponor Smart Aqua mounting angles and plates.



Item no.	Dimension	l1 mm	l2 mm	l3 mm	Rp inch	z1 mm	z3 mm	k mm	Qty 2	Qty 1	UOM
35001070638	16-Rp $\frac{3}{4}$ "FT	41	17	22	$\frac{3}{8}$	21	11	40	40	10	pce
35001070639	16-Rp $\frac{1}{2}$ "FT	41	17	22	$\frac{1}{2}$	21	7	40	40	10	pce
35001070640	20-Rp $\frac{1}{2}$ "FT	42	17	23	$\frac{1}{2}$	21	8	40	40	10	pce
35001070641	20-Rp $\frac{3}{4}$ "FT	45	17	23	$\frac{3}{4}$	24	7	40	20	5	pce
35001070642	25-Rp $\frac{3}{4}$ "FT	54	27	25	$\frac{3}{4}$	26	8	40	20	5	pce

Uponor S-Press PLUS tap elbow L


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- for on wall installation or attachment with rotation protection to the Uponor Smart Aqua mounting angles and plates.



Item no.	Dimension	l1 mm	l2 mm	l3 mm	Rp inch	z1 mm	z3 mm	k mm	Qty 2	Qty 1	UOM
35001070644	16-Rp $\frac{1}{2}$ "FT	42	20	30	$\frac{1}{2}$	22	15	40	40	10	pce
35001070645	20-Rp $\frac{1}{2}$ "FT	46	20	30	$\frac{1}{2}$	25	15	40	40	10	pce

Uponor S-Press PLUS sound + leak protect

- Set is suitable for two Uponor S-Press PLUS tap elbows 16-Rp $\frac{1}{2}$ "FT or 20-Rp $\frac{1}{2}$ "FT
- Pins and screws M6 x 16 included
- Made of EPP
- Sound protection acc., VDI 4100
- Drainage function conform to DIN 18534




Item no.	Dimension	l1 mm	l2 mm	z1 mm	Qty 2	Qty 1	UOM
35001121193	16-20	20	74	3	192	1	set
35001121194	16-20	23	71	3	192	1	set

Uponor S-Press PLUS

Uponor S-Press PLUS U-tap elbow


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- For on wall installation or attachment with rotation protection to the Uponor Smart Aqua mounting angles and plates.



Item no.	Dimension	l1	l2	l3	l4	Rp	z1	z2	z3	z4	b	k	Qty 2	Qty 1	UOM
35001070629	16-Rp½"FT-16	56	56	20	23	½	36	36	8		45	40	20	5	pce
35001070630	20-Rp½"FT-20	57	57	20	23	½	36	36	8		45	40	960	5	pce
35001070631	20-Rp½"FT-16	57	56	20	23	½	36	36	8		45	40	960	5	pce
35001070632	16-Rp½"FT-20	56	57	20	23	½	36	36	8		45	40	960	5	pce
35001070633	25-Rp½"FT-25	64	64	27	24	½	36	36	9		60	40	576	3	pce
35001070634	25-Rp½"FT-20	64	57	27	24	½	36	36	9		60	40	576	3	pce

Uponor S-Press PLUS tap elbow twin 90 long


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- For on wall installation or attachment with rotation protection to the Uponor Smart Aqua mounting angles and plates.
- Thread acc. to EN ISO 228-1



Item no.	Dimension	l1	l2	l3	l4	Rp	z1	z2	z3	k	k1	Qty 2	Qty 1	UOM
35001070648	16-Rp½"FT-16	44	45	30	20	½	24	25	15	20	20	40	10	pce
35001070649	20-Rp½"FT-20	46	46	30	20	½	24	25	15	20	20	40	10	pce

Uponor S-Press PLUS stop end

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access




Item no.	Dimension	l	l1	l2	Qty 2	Qty 1	UOM
35001070621	16	27	7	20	160	40	pce
35001070622	20	28	7	21	7680	20	pce
35001070623	25	35	7	28	3840	10	pce
35001070624	32	35	7	28	1920	5	pce

Uponor S-Press PLUS

Uponor S-Press PLUS adapter wall penetr.


- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- For lead-through through walls.
- Dimensions of attachment plate (H x W x D) 100 x 50 x 2 mm.
- Hole circle diameter 33 mm.



Item no.	Dimension	l	l1	l2	l3	s	Rp	z1	k	Qty 2	Qty 1	UOM
35001070652	16-G½"FT	51	17	20	100	2	½	14	40	5	1	pce

Uponor S-Press PLUS adapter

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- With soldered copper pipe according to EN 1057 (half hard / R250)
- complete tin-plated
- Attention:
The copper side is for press connections and suitable compression fittings only.




Item no.	Dimension	l	l1	l2	z1	Qty 2	Qty 1	UOM
35001070615	16-15CU	76	40	20	16	160	20	pce
35001070707	20-15CU	76	39	21	16	3840	10	pce

Uponor S-Press PLUS


Uponor S-Press PLUS mounting plate

- Made of galvanized steel.
- For the installation of Uponor Smart Aqua tap elbows
- Positioning of the connections in the given raster
- Plastic pins and loss protected screws M6x12 acc. DIN 965 included
- With holes and slots for easy attachment



NEW

Item no.	Dimension	l mm	s mm	h mm	k mm	k1 mm	w mm	Qty 2	Qty 1	UOM
35001121197	80/150mm	265	3	9	80	150	35	5	1	pce




Uponor S-Press PLUS mounting angle

- Made of galvanized steel.
- For the installation of Uponor Smart Aqua tap elbows
- Positioning of the connections in the given raster
- Plastic pins and loss protected screws M6x12 acc. DIN 965 included
- With holes and slots for easy attachment



NEW

Item no.	Dimension	l mm	s mm	b mm	h mm	k mm	k1 mm	w mm	Qty 2	Qty 1	UOM
35001121195	80/150mm	440	3	266	57	80	150	35	5	1	pce




Uponor Smart Aqua single mounting angle

- Made of galvanized steel.
- For the installation of Uponor Smart Aqua tap elbows.
- Positioning of the connections in the given raster.
- Screws M6x12 acc. DIN 965 included. With holes and slots for easy attachment




Item no.	Dimension	l mm	b mm	h mm	Qty 2	Qty 1	UOM
35001057843		144	82	46	5	1	pce



Uponor S-Press PLUS

Uponor Smart Aqua mounting rack


- Made of galvanized steel.
- For the installation of Uponor Smart Aqua tap elbows.
- Positioning of the connections in the given raster.
- Screws M6x12 acc. DIN 965 included. With holes and slots for easy attachment



Item no.	Dimension	l mm	k mm	Qty 2	Qty 1	UOM
35001057844	2m	2000	75	10	1	pce

Uponor Smart Aqua 10 pins+20 screws

- Pins and screws for mounting plates, angles and tracks.



Item no.	Dimension	l mm	do1 mm	do2 mm	c/c1 mm	Qty 1	UOM
35001057847*		17	4	10	10	1	set



Uponor GmbH

P.O. Box 1641
97433 Hassfurt
Germany

Australia

T +49-(0)9521 690 0
F +49-(0)9521 690 750
E international@uponor.com

T +61 (0)7 3202 6831
M +61 (0)477 136 977
E international@uponor.com

