



Type 515 Rotor-X
Wet-Tap Mount Paddlewheel (use with Type 3519 wet tap valve)

Flow:

- Operating range: 0.3 to 6 m/s, 1 to 20 ft/s
- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Max Pressure rating: PP 12.5 bar @ 20 °C, 180 psi @ 68 °F PVDF 14 bar @ 20 °C, 200 psi @ 68 °F
- Power source: Self powered
- Compatibility: 8150, 8900, 9900, 9900-1BC, 9950

MFR #	Body	Rotor Pin	Pin	Sensor Type	Pipe Size (inch)	DN-DN* (mm)	Code
P51530-P3	PP	Black PVDF	Titanium	Remote Mount	0.5 - 4.0	15-100	198 840 310
P51530-P4	PP	Black PVDF	Titanium	Remote Mount	5.0 - 8.0	125-200	198 840 311
P51530-P5	PP	Black PVDF	Titanium	Remote Mount	10.0 - 36.0	250-900	198 840 312

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>