



## Type 525 Metalex (use with Metalex Weld-On Mini-Tap, Socket Weld Mini-Tap)

### Flow:

- Installs into pipe sizes: 0.5 to 12 in, DN15 to DN300
- Operating range: 1.6 to 20 ft/s, 0.5 to 6 m/s
- Max Pressure rating: Socket weld or weld on fittings 103 bar, 1500 psi (@ safety factor 1.5)
- Power source: Self powered
- Compatibility: 8150, 8900, 9900, 9900-1BC, 9950

MFR #	Body	Rotor Pin	Pin	Pipe Size (inch)	DN-DN (mm)	Sensor Type
P525-1	Stainless steel	Stainless steel	Tungsten Carbide	0.5 - 1	15 - 25	Remote Mount
P525-2	Stainless steel	Stainless steel	Tungsten Carbide	1.25 - 12	32 - 300	Remote Mount
P525-1S	Stainless steel	Stainless steel	Stainless steel	0.5 - 1	15 - 25	Remote Mount
P525-2S	Stainless steel	Stainless steel	Stainless steel	1.25 - 12	32 - 300	Remote Mount

MFR #	Code
P525-1	<b>198 801 494</b>
P525-2	<b>198 801 495</b>
P525-1S	<b>159 000 963</b>
P525-2S	<b>159 000 964</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:  
info.ps@georgfischer.com Internet: <http://www.gfps.com>